

MITEL NETWORKS

5001 | IP Phone

Delivering the Power of IP Affordably



Low-Cost, Single-Line IP Phone

You recognize the power of Voice-over-IP to deliver personalized communications and productivity tools to your users. But the fact is some users and some areas of your operation require only basic access to voice and network features. So why invest in features they'll never use? Choose the Mitel Networks™ 5001 IP Phone instead. Part of the industry's most extensive line of IP desktop phones and devices, the Mitel Networks 5001 IP Phone is a low-cost, single-port IP telephone. It's ideal for any user or location requiring basic call handling and feature access to Mitel Networks 3100 and 3300 Integrated Communications Platforms (ICP). You pay only for the features your users need and they get an IP phone that offers the same ease of use, quality and reliability that is the hallmark of the entire Mitel Networks desktop portfolio.

For Occasional Users and Common Areas

The 5001 IP Phone is designed for occasional and non-communications intensive users requiring access to basic telephone and messaging services. It is the affordable choice for common areas such as receptions and meeting areas, manufacturing and retail floor, plus offices of non communications-intensive users. Like all Mitel Networks IP telephones and appliances, the 5001 IP Phone can be easily programmed and personalized with a web browser-based configuration tool.

Features*

- 4 function keys: Hold, Message Access, Transfer/Conference or Redial, Ringer Volume
- Placing calls on hold
- Transferring calls
- Setting up conference calls
- Voice mail access – large message waiting lamp
- Ringer volume control
- Web browser desktop configuration tool



Voice QoS

Supports 802.1p/q for quality of service.

Powering Options

Available with optional Ethernet/AC wall adapter and accepts standards-based (IEEE 802.3af) power over the LAN via spare or signal pair.

Ergonomic/Physical Features

- Wall Mountable
- Small Footprint – 8" x 6.9"
- Available in Dark Charcoal Gray and Light Dove Gray

System Requirements

- Mitel Networks 3100 Integrated Communications Platform, Release 3
- Mitel Networks 3300 Integrated Communications Platform, Release 3.1

Environmental Conditions

Temperature:	Humidity:
+4° C - +40° C (Operational)	34%
-25° C - +66° C (Storage)	15%

Regulatory Standards

EMC:	CLASS B (FCC-Part 15)
Network:	FCC-Part 68 (US) CS-03 (Canada)

5005 IP Phone Specifications

Ports	AC Adapter	Consumption	Processor Type	Processor Speed	Silicon	Package
1	Output: 48Vdc 250mA Input: 110V 60Hz	1.7W	ARM7TDMI	25MHz	0.18u CMOS	QFP
Voice Traffic	Signaling	Ethernet	Size (LxW)	Weight	MTBF Rate	Compression
RTP over UDP	Minet over TCP	IEEE 802.1p/q	8.5" x 6.9"	2.4 lbs	10 Years	G.711

*Not all features are supported across all IP Platforms. Please refer to the Mitel Networks 3100 Integrated Communications Platform (ICP) brochure and the Mitel Networks 3300 Integrated Communications Platform (ICP) brochure for more detailed information.

www.mitel.com

1-800-648-3579

Mitel Networks

350 Legget Drive
Ottawa, Ontario
K2K 2W7 Canada
(613) 592-2122

Mitel Networks, Inc.

205 Van Buren Street
Suite 400
Herndon, VA
20170-5336 USA
(703) 318-7020

Mitel Networks Ltd.

Mitel Business Park
Portskewett, Caldicot
NP26 5YR UK
Sales: 0870 9093030
General: 0870 9092020
Int: +44 (0) 1291 430 000



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2002, Mitel Networks Corporation. All Rights Reserved. GD 5364

PN 51003887, Rev. A